

Interactive
Comment

Interactive comment on “Aggregate breakdown and surface seal development influenced by rain intensity, slope gradient and soil particle size” by S. Arjmand Sajjadi and M. Mahmoodabadi

A. Cerdà (Editor)

artemio.cerda@uv.es

Received and published: 11 February 2015

Dear author I found the paper ready to publish See minor suggestions attached
Sincerely Artemi Cerdà

Please also note the supplement to this comment:

<http://www.solid-earth-discuss.net/6/C1595/2015/sed-6-C1595-2015-supplement.pdf>

Interactive comment on Solid Earth Discuss., 6, 3303, 2014.

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

Discussion Paper



Aggregate breakdown and surface seal development influenced by rain intensity,**slope gradient and soil particle size**

Sara Arjmand Sajjadi and Majid Mahmoodabadi

Dep. of Soil Sci., Agriculture Faculty, Shahid Bahonar University of Kerman, Kerman,
Iran. Tel. +98 34 31322651; Fax: +98 34 33222043

E-mail: sara.arjmand.1986@gmail.com

E-mail: mahmoodabadi@uk.ac.ir

Corresponding Author: Majid Mahmoodabadi

Abstract

Aggregate breakdown is an important process which controls infiltration rate (IR) and the availability of fine materials necessary for structural sealing under rainfall. The purpose of this study was to investigate the effects of different slope gradients, rain intensities and particle size distributions on aggregate breakdown and IR to describe the formation of surface seal. To address this issue, 60 experiments were carried out in a 35×30×10 cm detachment tray using a rainfall simulator. By sieving a sandy loam soil, two sub-samples with different maximum aggregate sizes of 2 mm ($D_{max}2mm$) and 4.75 mm ($D_{max}4.75mm$) were prepared. The soils were exposed to two different rain intensities (57 and 80 mm h⁻¹) on several slopes (0.5, 2.5, 5, 10, and 20%) each at three replicates. The result showed that for all slope gradients and rain intensities, the most fraction percentages in soils $D_{max}2mm$ and $D_{max}4.75mm$ were in the finest size classes of 0.02 mm and 0.043 mm, respectively. The soil containing finer aggregates exhibited higher transportability of pre-detached material than the soil containing larger aggregates. Also, IR increased with increasing slope gradient, rain intensity and aggregate size under unsteady state conditions because of less development of surface

Fig. 1.

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

Discussion Paper

